Canadian Journal of Fisheries and Aquatic Sciences
Journal canadien des sciences halieutiques et aquatiques

**On the precision of predicting fishing location using data
from the Vessel Monitoring System (VMS)**

Journal:	<i>Canadian Journal of Fisheries and Aquatic Sciences</i>
Manuscript ID	cjfas-2016-0446.R2
Manuscript Type:	Article
Date Submitted by the Author:	22-Jul-2017
Complete List of Authors:	Muench, Angela; NOAA Northeast Fisheries Science Center, Social Science Branch DePiper, Geret; NOAA Northeast Fisheries Science Center, Social Science Branch Demarest, Chad; NOAA Northeast Fisheries Science Center, Social Science Branch
Is the invited manuscript for consideration in a Special Issue? :	N/A
Keyword:	VMS, precision, fishing location

SCHOLARONE™
Manuscripts

On the precision of predicting fishing location using data from the Vessel Monitoring System (VMS)

Angela Muench¹, Geret Sean DePiper² and Chad Demarest³

September 2017

Abstract

Defining fishing grounds based on data from Vessel Monitoring System (VMS) has been a widely-researched topic in recent years. Much of the research has focused on filtering algorithms for identifying fishing locations from VMS point data, most often supplemented with either imputed or reported vessel speed information. This study compared the precision of categorizing fishing locations from VMS data either by the most wide-spread ‘speed rule’ approach or a probability model. Using data from Northeast U.S. Fisheries for fishing years 2010-2014, we showed that the traditional representation of fishing activities as derived by speed rules leads to a severe misrepresentation of fishing grounds for gears other than bottom otter trawl. Predictions based on probability models outperformed gear-specific speed rules in classifying VMS polls for sink gillnet and scallop dredge trips, without adding substantial computational effort. The probability models thus provide the largest improvements in gears with complicated fishing patterns, while controlling for issues, such as fleet dynamics, that historically have not been dealt with in the static speed rules, but which can have significant impacts on the quality of predictions.

JEL: Q22

Keywords: VMS, precision, fishing location

- 1 Corresponding author: Integrated Statistics, 16 Sumner Street, Woods Hole Massachusetts, 02543 USA, under contract to: Northeast Fisheries Science Center, National Marine Fisheries Service, National Oceanic and Atmospheric Administration, 166 Water Street, Woods Hole, MA 02543, USA, E-mail: angela.muench@cefas.co.uk¹
- 2 Northeast Fisheries Science Center, National Marine Fisheries Service, National Oceanic and Atmospheric Administration, 166 Water Street, Woods Hole, MA 02543, USA, E-mail: geret.depiper@noaa.gov

¹ Current affiliation: Centre for Environment, Fisheries and Aquaculture Science (CEFAS), Pakefield Road, Lowestoft, Suffolk NR33 0HT, UK, E-mail: angela.muench@cefas.co.uk, Tel: +44 150 2524293

- 3 Northeast Fisheries Science Center, National Marine Fisheries Service, National Oceanic and Atmospheric Administration, 166 Water Street, Woods Hole, MA 02543, USA E-mail: chad.demarest@noaa.gov

Draft

1 Introduction

2 Vessel Monitoring Systems (VMS) are satellite-based surveillance systems that send vessel
3 identification and location (the VMS poll) information at pre-specified time intervals, often
4 for fishery enforcement. In the Northeastern U.S., VMS is used in part because human
5 observers are cost prohibitive and impractical to deploy on every trip. Globally, there is a
6 desire to use VMS data for fine-scale fishing location information. Likewise, in the
7 Northeastern U.S. fine scale fishing location data from VMS units may augment self-reported
8 fishing location data, where fishermen are only required to report one fishing
9 latitude/longitude per logbook entry. For example, a bottom trawler in our data reported a
10 single latitude/longitude for a 13-days trip traveled roughly 1 300 km and included 50 hauls.
11 The spatial coarseness of the logbook data creates substantial imprecision in determining
12 relevant spatial metrics (e.g. biomass removals, habitat impacts, etc.), and this underlies the
13 need for VMS-based analysis.

14 The most common method to classify VMS polls as fishing, as the data itself do not directly
15 indicate this, is the speed rule. This method classifies VMS as fishing if the vessel speed falls
16 within a specific range. VMS-based speed rules have been used to evaluate the seabed impact
17 of demersal fishing (Diesing et al. 2013; Gerritsen et al. 2013), assess the impact of closures
18 on cod in Scotland (Needle and Catarino 2011), calculate stock allocations in the northeastern
19 US fisheries (Palmer and Wigley 2009), and identify spawning areas of blue ling in the UK
20 (Large et al. 2010). Depending on the fishery and the specific thresholds employed, speed
21 rules have demonstrated high rates of true-positives often are connected to high rates of false-
22 positives. So, for example, Skaar et al. (2011) obtained for their small sample of demersal
23 stern trawlers in the Barents Sea a true-positive rate of 75-80 percent and only a false-positive
24 rate of 10-15 percent. In contrast, Gerritsen and Lordan (2011) correctly predicted 88 percent
25 of fishing polls for the Irish otter trawl fleet, while at the same time a false-positive rate of 68

percent was generated. More strikingly, O'Farrell et al. (2017) attained a true-positive rate of only 49 percent but a false-positive rate of 95 percent when employing speed rules in the Gulf of Mexico bandit-reel fishery.

The appropriate speed rule depends on the characteristics of the fleet of interest, including size and horsepower of the vessels, gear employed, species targeted, depth of fishing, current strength, and wave size. These characteristics obviously vary greatly across management regions. Further, the elapsed time between polls may range from at least once an hour in the Northeastern U.S., to two hours in much of Europe (EC 2009; Murray et al. 2011) and every six hours in certain Taiwanese fleets (Chang and Yuan 2014). These differences lead to data variation which hinders the simple transfer of speed rules across fleets or regions.

This study developed a probability model for VMS polls applicable across gear groups and robust to variable polling frequencies. Although not the first statistical approach employed (e.g. Vermard et al. 2010; Walker and Bez 2010; de Souza et al. 2016), the generalized linear model (GLM) framework presented here is amenable to large datasets and varying polling frequencies that can prove problematic to Bayesian techniques (Peel and Good 2011; Banerjee and Fuentes 2012), with only a small increase in implementation complexity over speed rules. We assess probability models for three fishing gear types with a focus on their ability to correctly predict both fishing and non-fishing activity, and find that these models provide substantial performance gains relative to speed rules for two of three gears.

Materials and Methods

Data

This study used data from the Northeast U.S. Fisheries for the fishing years 2010 - 2014. The analysis was restricted to the three main gear groups employed in the region: (1) scallop dredges, (2) sink gillnet, and (3) bottom otter trawl. VMS data were merged with logbook

50 data (Vessel Trip Reports - VTR) to assign the fishing gear employed to each VMS poll in
51 the dataset. The data was also linked to the Northeast Fisheries Observer Program (NEFOP)
52 and the At-Sea-Monitoring Program (ASM) datasets, which were compiled by on-board
53 human monitors that identify the start and end times of the fishing hauls.

54 Vessels were required to have a VMS on board if their commercial fishing activity was
55 subject to a Fishery Management Plan with a VMS requirement. Relevant for federal
56 management and this study was only the fishing activity within the exclusive economic zone
57 (EEZ) and conducted after the vessel crossed VMS demarcation line (approximately three
58 nautical miles from shore). Although, there were some exceptions (e.g. scallop rotational area
59 trips and groundfish trips exploiting the shared US/Canada resource), most vessels were
60 obliged to send their positions once an hour, and at increased intervals when the vessel
61 approached fishing closures.

62 This research focused on VMS signals that could be temporally linked to an active
63 commercial fishing trip according to the VTR (Bastardie et al. 2010). Due to the time gap
64 between VMS signals, the VTR/Observer data were merged with the VMS data by date and
65 time, with a deviation of one hour to capture VMS signals shortly before and after the self-
66 declared start and end of the trip as defined in the vessel's VTR. According to the VTR
67 records, in total more than 108 000 bottom otter trawl, ca. 73 000 sink gillnet, and 44 000
68 scallop dredge trips occurred in the period under consideration. However, not all of these
69 trips were required to have a VMS transponder on board. Furthermore, only a fraction of trips
70 was required to take a human observer on board (ca. 15 percent, but varies widely between
71 fisheries). Our final dataset, the combined logbook, VMS, and observer data, represents ca.
72 eight percent of all commercial bottom otter trawl trips, ten percent of all commercial sink
73 gillnet trips, and five percent of all commercial scallop dredge trips for the given period -
74 coverage that was driven primarily by observer coverage requirements and, importantly, not

75 by failure to match trips across data sets. Although this coverage of commercial fishing trips
76 may seem low, the bottom otter trawl dataset consisted of about 930 000 VMS polls, the sink
77 gillnet dataset of about 147 000 VMS polls and the scallop dredge dataset of about 550 000
78 VMS polls, presenting an abundance of data. Further, the probability model was based
79 predominantly on the physical characteristics of fishing activities which are mechanistic in
80 nature and unlikely to be affected by fisherman's strategic behavior when observed. All VMS
81 polls of trips with data inconsistencies (e.g. new trip starts before last trip ends, or VMS
82 signals generating imputed speeds above 40 km/h) or not having enough data for reliable
83 estimation (e.g. only one VMS poll per trip, trip duration is less than one hour, or no
84 observed fishing activity was captured by any of the VMS polls within the trip) were
85 excluded. VMS polls were also removed from the dataset if there was less than one meter
86 movement between two consecutive polls belonging to the same trip or if all polls belonging
87 to one trip were only located between shore and VMS demarcation line, to focus on federal
88 fishing activities. Cleaned VMS data included duplicates in coordinates (i.e. about 7 percent
89 of the bottom otter trawl VMS polls, 4 percent of the scallop dredge VMS polls and 3.5
90 percent of the sink gillnet VMS polls) which were sent with different timestamps, but likely
91 overlap due to imprecision in the transmitted location. These duplicated coordinates were
92 excluded from the analysis.

93 VMS polls were identified as *observed* fishing polls if their timestamp fell within the time
94 range of an observed fishing haul according to the onboard observer. The observed VMS
95 fishing polls were the baseline for the comparison between the speed rule and probability
96 models conducted in this study. It should be noted that the ratio of fishing polls to non-fishing
97 polls in the observed VMS data differed substantially between gear groups. For bottom otter
98 trawlers, the ratio of fishing to non-fishing VMS polls averaged 1.3 across the study period,
99 while the same ratio was about 0.9 for scallop dredges and 0.5 for sink gillnetters. These

differences were driven by differences in fishing practices, particularly with regards to the duration of fishing hauls and length of trips (predominantly one-day trips for sink gillnetters vs. multi-day trips for bottom otter trawlers or scallop dredges). Moreover, bottom otter trawlers tended to fish over long periods of time (averaging 3.3 hours) following relatively linear depth contour lines (Thomas-Smyth et al. 2015). In contrast, scallop dredges often followed a zig-zag course with shorter tow durations (averaging an hour), before circling back to their starting point. After the haul, scallop fishermen would sometimes stop the vessel to shuck (i.e. process) scallops and clear the deck (Hart and Rago 2006; Palmer and Wigley 2009). This created very different speed patterns of fishing in the data between the two gears. In comparison, sink gillnetters are considered a fixed gear, which means the vessels stop to haul anchored nets on board, empty the catch, and reset the nets. This fishing activity averaged less than an hour, meaning VMS polls fall within observed fishing activities less frequently than the other gears studied, an issue previously raised by O'Farrell et al. (2017). Unlike other systems, VMS in the Northeastern U.S. did not transmit the instantaneous speed or the bearing angle of the vessel, necessitating the calculation of imputed speeds and angles. Speed at the VMS poll was calculated as the average vessel speed (distance/time) from the lagged VMS poll assuming the vessel traveled in a straight-line between consecutive polls. The *difference in speed* between the imputed speed of the current and lagged-VMS polls was also derived for the analysis. The bearing *angle* of the current VMS poll heading towards the next VMS poll was estimated assuming a straight line between polls. The bearing angle was included in the analysis following the argument of Mills et al. (2007) that vessel bearing angle may help to characterize the activity of the vessel at a point in time, and has been used in numerous studies (Vermard et al. 2010; Bez et al. 2011; O'Farrell et al. 2017). To more precisely differentiate between fishing, anchoring, and steaming activities, an indicator variable *speed range* was computed, which took on a value of one if the imputed

speed of the current VMS poll deviated less than one kilometer per hour from the mean speed of the lag, current and lead VMS polls (O'Farrell et al. 2017). Given that speed was an imputed average at a point in time, the *speed range* indicator sought to capture the probability that a shift in activity occurred shortly before or after the current poll, while the continuous variable *difference in speed* captured the probability that the shift in activity occurred shortly after the proceeding poll.

Fishing is more likely to be observed in the middle of the fishing trip, as both the beginning and end of a trip tends to represent travel to and from port. To capture this non-linearity, a position weight and the squared accumulated distance of the trip were included. The *position weight* p_i was an inverse u-shaped function based on the position of the VMS poll within the trip, with a maximum of one and taking the form:

$$(1) \quad p_i = 1/(n_i - (N/2 + 1))^2 \text{ if } (n_i - (N/2 + 1)) \neq 0, \text{ else } p_i = 1.$$

Here n_i was an integer indicating the position of the VMS poll within a sub-trip and N denoted the total number of VMS polls belonging to the sub-trip. A trip was broken up into sub-trips if consecutive VMS polls had a deviation of less than one meter. As an example, if a sub-trip included 40 VMS polls, the first and last VMS poll received a position weight close to zero while VMS poll 21 received a position weight of one. Sub-trips were defined following similar logic to that employed when developing the indicators for abrupt speed changes. This weight only accounted for the VMS poll's relative position within the trip, but not for the distance or the time lag between VMS polls. Scheduled VMS polls were sometimes missing due to issues such as poor weather conditions. Additionally, VMS systems were used for ship to ship communications, and a VMS poll was sent each time the vessel used the VMS system as communication tool. This generated polls at higher frequency than would otherwise be expected. To account for the non-standard time frequency between

149 the VMS polls, the accumulated *distance* between the VMS polls based on the geodetic
150 distance was included (similar to O'Farrell et al. 2017). Assuming, as above, that the earlier
151 and latter part of the trips were steaming rather than fishing activities, and noting that
152 substantial travel was necessary to reach certain fishing locations, any non-linearity of the
153 likelihood of the fishing activity with respect to distance traveled was captured by including
154 the squared accumulated distance in addition to the position weight, without accounting for
155 sub-trips.

156 To capture the *depth* of the seabed at the vessel's location, the VMS poll was linked to its
157 closest coastal bathymetric contour line, measured in meters and based on data originating
158 from the U.S. Coastal Relief Model made available by the NOAA National Geophysical Data
159 Center. The depth of the seabed was included to capture target species ranges (NEFMC,
160 2016). For example, scallop dredges primarily target Atlantic sea scallops (*Placopecten*
161 *magellanicus*) which are harvested commercially predominantly at depths between 35-100
162 meters. Similar general rules regarding the depth of species target by sink gillnets and bottom
163 otter trawls apply. For example, black sea bass (*Centropristis striata*) is most often found at
164 less than 36 meters, monkfish (*Lophius americanus*) occurs primarily between 25-200
165 meters, and summer flounder (*Paralichthys dentatus*) range in depths up to 152 meters during
166 the spring, but in fall tend to occur at depths less than 61 meters. Hence, the depth variable
167 helped to distinguish between areas in which fishing was likely due to target species
168 abundance (in a similar manner to O'Farrell et al. 2017). A variable for the difference in
169 depth ($Depth - Depth_{t-1}$) captured the fact that mobile fishing gears tend to follow depth
170 contours while actively fishing (Thomas-Smyth 2015). Hence, large differences in seabed
171 depth were more likely to be associated with steaming instead of fishing.

172 Time-specific characteristics were captured by indicator variables denoting fishing year,
173 month, day of the week, and whether the VMS poll occurred during the day or night. Moon

phases were also included, as they can correlate to activity levels and other fish behavior (Henderson and Fabrizio 2011) which in turn could change optimal targeting and fishing behavior, or the tide might influence fishing location (e.g. Damalas et al. 2007). Because of this the moon phases of the night before and the night of the VMS poll were controlled for through another set of indicator variables. While moon phase dummies looked to capture cyclical changes in target species behavior that might in turn have affected fishing behavior, day of the week dummies identified cyclical market dynamics which might explain the probability of steaming versus fishing activity. For example, Lee (2014) indicates that demand for groundfish in New England is lower on Fridays, as processors tend to close over the weekend. This would suggest that groundfish fishermen were less likely to be steaming to shore on Fridays, when compared to other days of the week, changing the overall probability of a poll being associated with fishing activity.

Fishing speed is determined not only by the vessel gear and its size but also by the vessel's power. We controlled for this by incorporating the ratio of the vessel's horse power to its length ($VHP/length$). An interaction term between the vessel characteristic and imputed speed captured the interdependence between these characteristics for fishing activities.

To avoid scaling issues, continuous variables were z-standardized (subtracting the mean and dividing by the standard deviation of the respective variable) before entering the regression models. The descriptive statistics of the data in raw format can be found in Table A1 in the Appendix. The geographic distribution of the data by gear group was shown in Figs. 1-3.

Fishing activity prediction based on VMS data

Speed rule method

To separate VMS polls into fishing and non-fishing activities, Palmer and Wigley (2009) developed a gear-specific speed rule for the same fleet as the present study using a different

period (i.e. calendar year 2005). We used their study as a point of departure for our analysis. Palmer and Wigley (2009) argue that VMS polls with an imputed speed in the range of 3.7-7.4 km/h for otter trawls, 4.6-11.1 km/h for scallop dredges and 0.2-2.4 km/h for sink gillnet generally represent fishing activity. Lee et al. (2010) claim that a speed range of 1-8 knots (i.e. 1.852 - 14.816 km/h), irrespective of the gear employed, reliably identifies fishing polls, and corresponding fishing locations. We compared the two speed rules to assess the predictive quality of these simple rules (i.e. true-positive and false-positive rates) compared to actual observed fishing locations (i.e. VMS polls related to fishing activities according to the human observer on board of the vessel).

Probability model

Instead of using speed rules, D. Records and C. Demarest (2013, unpublished manuscript) proposed the use of a GLM, specifically a logistic regression model, to estimate the probability a VMS poll corresponds to fishing activity based on observer data. The logistic regression estimates the log odds of the probability of "fishing", which depends on a set of p explanatory variables $X=(X_1, X_2, \dots X_p)$. The dependent variable y_i equals one if the VMS poll occurs during a known fishing period and zero otherwise. More formally, this relationship is modeled as:

(2)
$$\Pr(Y = 1 \mid X = x_i) = F(x, \beta) = \frac{e^{x'\beta}}{1+e^{x'\beta}} \quad (\text{Greene 2003}).$$

In this formulation, $Y = (y_1, y_2, \dots y_n)$, which took the value of 1 if poll $i \in (1, \dots, n)$ occurred during a known fishing event, and 0 otherwise, x_i were observed characteristics of poll i , and β were the parameters to be estimated. We estimated the probability of a VMS poll being a fishing poll based on the explanatory variables (X): *speed*, its square (*speed*²), difference in speed (*speed-speed_{t-1}*), deviation in speed (*speed range*), ocean depth (*depth*),

difference in ocean depth ($depth - depth_{t-1}$), turning angle ($angle$), *position weight*, the accumulated distance ($distance$), its square ($distance^2$), the vessel characteristic ($VHP/length$), an interaction term between vessel power characteristic and speed ($VHP/length \times speed$) and temporal dummies (for e.g. fishing year, month, day of the week, time of the day, and moon phase). The model stability, quality, and convergence characteristics were assessed by calculating the variance inflation factor for the matrix of independent variables, as well as the gradients and the condition number of the estimation models, following McCullough and Vinod (2003) and Greene (2008). The estimation results were thus investigated for potential biases and convergence issues due to multicollinearity and over-specification. We tested the residuals of the estimation for spatial and serial correlation. Spatial correlation in the residuals were assessed by calculating Moran's I (assessing global spatial correlation) and Geary's C (assessing local spatial correlation) for the 15 nearest neighbors. Results were robust to changes in the number of neighbors used. We tested for serial autocorrelation by calculating and assessing Durbin-Watson statistics, following Baltagi (2011) who notes that serial correlation does not bias the coefficient estimation but inflates the standard error in a similar manner to multicollinearity. To guard generally against biased standard errors, we calculated the standard error based on a heteroscedasticity and autocorrelation consistent covariance matrix (i.e. sandwich method as described in Greene 2008). The models were further estimated separately for each gear group to allow for difference in the coefficients of the explanatory variables between gears.

We randomly drew 50 percent of trips for each fishing year and reserved their corresponding VMS data to fit the GLM. The remaining data was used to generate out-of-sample predictions to validate our estimates. To avoid potential sampling bias, we repeated the random draw of trips twenty times. According to Greene (2008) the difference in the predicted probability should be small if the variation in the sample data is low. Hence, if sampling bias or outliers

(i.e. high leverage) were an issue, both the coefficient and the predicted values should deviate significantly. This process (including the number of repeats) was similar to the iterative bootstrap approach used by O'Farrell et al. (2017) to assess the prediction quality of their training data approach. We chose twenty draws, a number sufficient to detect sampling bias if it existed.

Comparing speed rule approach with probability model prediction quality

The predictions of the deterministic speed rule approaches were compared to the predictions of the probability models using Receiver Operating Characteristics (ROC) graphs and the Area Under its Curve (AUC) following Fawcett (2006). The ROC is a two-dimensional graph, which plots the sensitivity (true-positive rate) and specificity (1-false-positive rate) of different prediction methods against each other while continuously increasing the cutoff-threshold. This methods allows a direct comparison of the predictive quality of differing methods. However, the speed rule methods provided only one true-positive and false-positive number for each approach. To compare the speed rule approaches with the probability model, this one point was connected by a direct line with the (0, 100) and (100, 0) point of the graph to create comparable ROC curves as well as to calculate the AUCs. The approach with the best predictive quality is the one with the most upper-left extent in the ROC graph. However, as curves may overlap and the direction 'Top-Left' is a rather flexible definition, the AUC provided a more precise measure of the prediction quality. The method which generates the largest AUC delivers the highest predictive quality.

As each observation was predicted anywhere from one to twenty times, we randomly drew a single predicted value for each observation. These randomly selected observation predictions formed the basis for constructing the ROC curve to which each corresponding speed rule's curve was compared. The 95 percent confidence intervals for the GLM predictions were used

as lower and upper bounds of the ROC curve (GLM-ROC). The cutoff threshold was determined by the Youden's J statistic (Youden 1950) based on the predicted GLM-ROC. The threshold was fixed for the ROC created by the speed rule approaches in order to assess the true-positive and false-positive rates at this cutoff point for these approaches (Table 4). Maps were drawn using the Youden's J statistic as the cutoff-point, based on the GLM predictions (Figs. 1-3). We did not include similar maps for speed rule determined fishing locations, as on this scale the differences between maps were not observable.

Apart from calculating a threshold on the fitted value with the help of the Youden J statistic, another way of using the derived fitted values from the probability model was to use a trip-specific threshold (e.g. trip-specific average of predicted values). Generating a trip-specific threshold provided control for trip-level unobserved characteristics which, due to the sheer number of trips, cannot directly be controlled for in the GLM estimation. For example, weather and other environmental effects may lead to variation in haul characteristics, even if hauls were conducted by the same crew, gear, and vessel, targeting the same species. A trip specific threshold was a theoretically simple way to capture trip-individual effects which should improve prediction quality noting that similar approaches were not possible using the speed rule approach. In the following, we implemented a trip specific threshold defined as the trip mean probability value for bottom otter trawl and scallop dredges and the 45th percentile for sink gillnet trips. This difference in threshold was designed to create true-positive rates above 80 percent without raising the false-positive rate about 50 percent, an implicit goal of the co-authors. While the trip average met this goal for scallop dredge and bottom otter trawl trips, the sink gillnet trip threshold needed to be adapted slightly to increase predictive performance, highlighting the complexity in creating a single approach which performs well across different fisheries.

Robustness-check: daytime and parsimonious models

Beyond investigating potential sampling bias through resampling, the stability of the probability model was further assessed by excluding insignificant variables if they were not part of an interaction term (Brambor et al. 2006). The parsimonious scallop dredge model was assessed through iterative bootstrapping in the same manner as the full model, excluding the difference in speed, depth, position weight, distance, and weekday variables. The parsimonious model for sink gillnet trips excluded the explanatory variables weekday, difference in depth, position weight, and the interaction term of VHP/length $\times$ speed, while the estimation for the parsimonious model for bottom otter trawl data did not include the variables weekday and bearing angle.

Although the explanatory variable daytime was significant in all three probability models, as a further robustness check it was removed from the regression because human observers may observe less hauls at night time, a time they normally sleep. Using time of day as an explanatory variable might bias the results.

Results

Probability models

For bottom otter trawl and scallop dredges the speed variable and its non-linear formation (speed²) dominated the probability prediction of the estimation models (Tables 1 and 3). However, for sink gillnet trips the daytime variable was the major driver in the estimation model (Table 2). Nevertheless, the parsimonious sink gillnet estimation model, which excluded the daytime, provided similar estimation results. In general, the coefficients and the predictive performance deviated only slightly between the full and parsimonious estimation models. While the weekday variable for ‘Thursday’ was still significant for bottom otter trawl in the full model, it was insignificant in the parsimonious model, hence all weekdays

variables were taken out of the parsimonious model regression. However, a likelihood ratio test comparing the parsimonious against the full model indicated that the individually insignificant variables excluded in the parsimonious model significantly improved the explanatory power of the full model. We used the predicted probability of the full models in the following comparisons, and noted that we found no indication of heteroscedasticity in the results (see diagnostics in Table 1-3).

Comparison of probability models and deterministic speed rules

The ROC curves (Figs. 4 and 5) indicated that the GLMs for the scallop dredge and sink gillnets outperformed the speed rules by up to 30 percent considering the difference in AUC values (Table 4). Specifically for sink gillnets, the speed rule of Lee et al. (2010) performed worse than a random equal probability classification of polls, with a ROC curve below the 45 degree line (Fig. 5). Conversely, for bottom otter trawl, a comparison of ROC curves created by the speed rule of Palmer and Wigley (2009) and GLM indicated that there were a small number of cut-off thresholds in which the two approaches had a similar predictive performance (Fig. 6). However, the AUC of the GLM-ROC was about 6 percent higher than the one of the ROC based on the speed rule of Palmer and Wigley (2009). In general, the GLM generated the maximum AUC for all three gear groups (Table 4), meaning it is the most accurate prediction method. Although the Palmer and Wigley (2009) gear-specific speed rule for bottom otter trawl performed well, the probability model resulted in more stable results overall.

Visually comparing the maps of observed fishing locations to the GLM predicted fishing locations (Figs. 1-3) indicated that the GLM overpredicted fishing activities in closed areas (in particular for the otter bottom trawl) or closer to the shore (in particular for the scallop dredges).

A comparison of predictions using ROC-curves at the optimal cutoff-point identified by the Youden's J statistic, we found for scallop dredges that the GLM generated a 15.8 percent higher true-positive rate than the speed rule of Palmer and Wigley (2009) and only increased the false-positive rate by 2.25 percent (Table 4). The GLM approach generated the highest accuracy for the sink gillnetters, resulted in a 39 percent higher true positive rate and 7.8 percent lower false-positive rate compared to the rates determined by the speed rule from Lee et al. (2010). For bottom otter trawl, however, both the true-positive rate and false-positive rate was increased by a comparable magnitude using the GLM approach instead of the speed rule approach of Palmer and Wigley (2009).

Employing trip specific thresholds led to similar results to those obtained using Youden's statistics as the cutoff (Table 4). While for the scallop dredge and sink gillnet estimations the false-positive rate increased slightly, the trip specific threshold raised the true-positive rate for bottom otter trawlers. The speed rule of Lee et al. (2010) remained to perform worst of all approaches, in particular with regards to sink gillnetters.

Discussion

This paper investigated the ability of a GLM to accurately predict observed fishing activity, while guarding against misclassification of non-fishing as fishing, for VMS data. The GLM prediction results were compared to the most widely used alternative approach, the VMS speed rule, for the same datasets and gear groups. For all three gears studied, the GLM outperformed a generic speed rule when predicting fishing activity of individual VMS polls. For bottom otter trawlers, the gear-specific speed rule can outperform the GLM in some instance. However, the GLM substantially outperformed the gear-specific speed rules for gears fishing in more complex patterns or for shorter durations, such as the zig-zag course of the scallop dredge vessels and the more stationary practices employed when fishing with fixed sink gillnet gear.

The GLM described in this research performed well in predicting fishing locations both in and out of sample for the analyzed gear groups, without the computational burden of the Markovian Process Models based on Bayesian inferences. An increase in the VMS frequency is likely to facilitate improved VMS analysis generally, as previously argued by e.g. Deng et al. (2015) or O'Farrell (2017). It is unclear whether there is political will to implement such a management measure in the Northeast US due to the increased costs associated with additional polling. The GLM, nevertheless, has been shown to effectively estimate and predict fishing activity for extremely large datasets, a challenge that may prove problematic for alternative techniques including engineering training and Bayesian approaches like Markovian Process Models. Moreover, the GLM is not dependent on a constant VMS poll transmission frequency, in contrast to the Markovian Process Models; however, it is dependent on the availability of observer data for the region and fishery under research to derive the estimation parameters. The simple speed rule tends to heavily misclassify activities for gear groups employing complex fishing patterns. Given the tractability and the relative ease of implementation of the GLM, there is no strong reason to choose the speed rule. A major caveat is that the GLM, like all statistical approaches, depends on observer data for estimation, which could limit its global application.

Further, as evidenced by our comparison of the Palmer and Wigley (2009) analysis, which was based on calendar year 2005 data, and the same rule applied to data for fishing year 2010-2014, static speed rules are likely to need temporal updating to reflect changes in fleet dynamics, reporting requirements, and management measures and other causes likely to induce shifts in fishing behavior. In their study, Palmer and Wigley (2009) found that their speed rule classified 99.2 percent of the fishing VMS polls correctly and reported a false-positive rate of 31.8 percent for bottom otter trawl trips. However, for the fishing years 2010-2014, the true-positive rates decreased to 82.8 percent and the false-positive rate to 19.0

percent. Similar changes in prediction quality over time can be noted for scallop dredge vessels. Palmer and Wigley (2009) reported a true-positive rate of 98.3 percent and false-positive rate of 69.3, we noted that using the same speed range with a our more recent dataset reduced the true-positive rate to 63.0 percent and false-positive rate to 36.1 percent. Hence, the speed rule seems to have lost validity over time. Changes in the composition of the fisheries and vessels monitored by VMS can induce shifts in the distribution of speeds surrounding fishing activity which may not be adequately captured by a static speed rule.

In future research, this analysis should be extended to other gears as it would lend additional insight into the general practicability of the approach for gear types with lower VMS coverage or for fisheries with fishing behavior that often falls in-between VMS polls (e.g. Gulf of Mexico bandit-reel fishery). Moreover, exploring the heterogeneity of fishing activity within gear groups seems a necessary further step to fully understand fishing activity and location choices. As we demonstrated, the GLM mildly outperformed the gear-specific speed rule for bottom otter trawls, and substantially outperformed the speed rule for sink gillnet and scallop dredge gears. For other fisheries using gears such as the purse seiner, hidden Markov models may better classify activities, given the movement patterns of the vessel while actively fishing (Vermard et al. 2010; Bez et al. 2011; de Souza et al. 2016). Nevertheless, for the gears studied in this paper the GLM provided a better understanding of fishing activities and improved the prediction of fishing locations for purposes such as impact assessments.

Although not explicitly used in this paper, the probability model provides additional information – specifically the estimated probability values themselves – which is not available from the simpler speed rules traditionally applied to VMS. These probability values can be used to spatially attribute fishing effort, catch, and revenue metrics in a manner that explicitly considers the uncertainty inherent in the data. Future research should more fully consider this added information.

417

Draft

References

- Baltagi, B.H. 2011. *Econometrics*, 5th Ed. Springer Verlag: Berlin-Heidelberg
- Banerjee, S. and Fuentes, M. 2012. *Bayesian Modeling for Large Spatial Datasets*. Wiley Interdisc. Rev.: Comp. Stat. 4: 59-66.
- Bastardie, F., Nielsen, J.R., Ulrich, C., Egekvist, J. and Degel, H. 2010. Detailed mapping of fishing effort and landings by coupling fishing logbooks with satellite-recorded vessel geo-location. *Fish. Res.* 106: 41-53.
- Bez, N., Walker, E., Gaertner, D., Rivoirard, J. and Gaspar, P. 2011. Fishing activity of tuna purse seiners estimated from vessel monitoring system (VMS) data. *Can. J. Fish. Aquat. Sci.* 68: 1998-2010.
- Brambor, T., Clark, W.E., and Golder, M. 2006. Understanding interaction models: improving empirical analyses. *Pol. Anal.* 14:63-82.
- Chang, S.-K. and Yuan, T.-L. 2014. Deriving high-resolution spatiotemporal fishing effort of large-scale longline fishery from vessel monitoring system (VMS) data and validated by observer data. *Can. J. Fish. Aquat. Sci.* 71: 1363-1370.
- Damalas, D., Megalofonou, P. and Apostolopoulou, M. 2007. Environmental, Spatial, Temporal, and Operational Effects on Swordfish (*Xiphias gladius*) Catch Rates of Eastern Mediterranean Sea Longline Fisheries. *Fish. Res.* 84: 233-246.
- De Souza, E.N. Boerder, K., Matwin, S. and Worm, B. 2016. Improving fishing pattern detection from satellite AIS using data mining and machine learning. *PloS One* 11:e0158248
- Deng, R., Dichmont, C., Milton, D., Haywood, M., Vance, D., Hall, N. and Die, D. 2005. Can vessel monitoring system data also be used to study trawling intensity and population depletion? The example of Australia's northern prawn fishery. *Can. J. Fish. Aquat. Sci.* 62: 611-622.

- Diesing, M., Stephens, D. and Aldridge, J. 2013. A proposed method for assessing the extent of the seabed significantly affected by demersal fishing in the Greater North Sea. *ICES J. Mar. Sci.* 70: 1085-1096.
- EC .2009. European Council Regulation (EC) No 1224/2009 of 20 November 2009. *Offic. J. EU*, 2009-12-22, L 343/1.
- Fawcett, T. 2006. An introduction to ROC analysis. *Pattern Recogn. Letters.* 27:861-874.
- Gerritsen, H.D. and Lordan, C. 2011. Integrating vessel monitoring systems (VMS) data with daily catch data from logbooks to explore the spatial distribution of catch and effort at high resolution. *ICES J. Mar. Sci.* 68: 245-252.
- Gerritsen, H.D., Minto, C. and Lordan, C. 2013. How much of the seabed is impacted by mobile fishing gear? Absolute estimates from Vessel Monitoring System (VMS) point data. *ICES J. Mar. Sci.* 70: 523-531.
- Greene, W.H. 2003. *Econometric Analysis*. 5th Ed., Pearson Education Inc: Upper Saddle River, NJ.
- Hart, D. and Rago, P. 2006. Long-Term Dynamics of U.S. Atlantic Sea Scallop *Placopecten magellanicus* Populations. *North. Am. J. Fish. Mana.* 26: 490-501.
- Henderson, M. and Fabrizio, M. 2011. *Migration Patterns of Adult Summer Flounder from Chesapeake Bay: Implications for Stock Structure*. Newport News, VA: Virginia Marine Resource Commission.
- Large, P.A., Diez, G., Drewery, J., Laurans, M., Pilling, G.M., Reid, D.G., Reinert, J., South, A.B., and Vinnichenko, V. I. 2010. Spatial and temporal distribution of spawning aggregations of blue ling (*Molva dypterygia*) west and northwest of the British Isles. – *ICES J. Mar. Sci.* 67: 494-501.

- Lee, J., South, A.B. and Jennings, S. 2010. Developing reliable, repeatable, and accessible methods to provide high-resolution estimates of fishing-effort distributions from vessel monitoring system (VMS) data. *ICES J. Mar. Sci.* 67: 1260-1271.
- Lee, M. 2014. Hedonic Pricing of Atlantic Cod: Effects of Size, Freshness and Gear. *Mar. Res. Econ.* 29: 259-277.
- McCullough, B.D. and Vinod, H.D. 2003. Verifying the Solution from a Nonlinear Solver: A Case Study. *Amer. Econ. Rev.* 93: 873-892.
- Mills, C.M., Townsend, S.E., Jennings, S., Eastwood, P.D. and Houghton, C.A. 2007. Estimating high resolution trawl fishing effort from satellite-based vessel monitoring system data. *ICES J. Mar. Sci.* 64: 248-255.
- Murray, L.G., Hinz, H. and Kaiser, M.J. 2011. Functional response of fishers in the Isle of Man scallop fishery. *Mar. Ecol. Prog. Ser.* 430: 157-169.
- Needle, C.L. and Catarino, R. 2011. Evaluating the effect of real-time closures on cod targeting. *ICES J. Mar. Sci.* 68: 1647-1655.
- New England Fishery Management Council (NEFMC) 2016. Omnibus Essential Fish Habitat Amendment 2, Vol I-IV, URL: <http://www.nefmc.org/library/omnibus-habitat-amendment-2> [accessed 21 July 2017].
- O'Farrell, S., Sanchirico, J.N., Chollett, I., Cockrell, M., Murawski, S., Watson, J.T., Haynie, A., Strelchek, A. and Perruso, L. 2017. Improving detection of short-duration fishing behaviour in vessel tracks feature engineering of training data. *ICES J. Mar. Sci.* 74: 1428-1436
- Palmer, M.C. and Wigley, S.E. 2009. Using Positional Data from Vessel Monitoring Systems to Validate the Logbook-Reported Area Fished and the Stock Allocation of Commercial Fisheries Landings. *North. Am. J. Fish. Mana.* 29: 928-942.

- Peel, D. and Good, N.M. 2011. A hidden Markov model approach for determining vessel activity from vessel monitoring system data. *Can. J. Fish. Aquat. Sci.* 68: 1252-1264.
- Russo T., Parisi A. and Cataudella S. 2011. New insights in interpolating fishing tracks from VMS data for different métiers. *Fish. Res.* 108:184-194.
- Skaar, K.L., Jørgensen, T., Ulvestad, B.K.H. and Engås, A. 2011. Accuracy of VMS data from Norwegian demersal stern trawlers for estimating trawled areas in the Barents Sea. – *ICES J. Mar. Sci.* 68: 1615-1620.
- Thomas-Smyth, A., Mamula, A., Speir, C. 2015. Assessing the Accuracy of High Spatial Resolution Effort Data: Comparing VMS and Logbook Data in the California Groundfish Trawl Fishery. Paper presented at the NAAFE Forum 2015, URI: <http://hdl.handle.net/1957/57647> [accessed 21 July 2017].
- Vermard, Y., Rivot, E., Mahevas, S., Marchal, P. and Gascuel, D. 2010. Identifying fishing trip behaviour and estimating fishing effort from VMS data using Bayesian Hidden Markov Models. *Ecol. Modell.* 221: 1757-1769.
- Walker, E. and Bez, N. 2010. A pioneer validation of a state-space model of vessel trajectories (VMS) with observers' data. *Ecol. Modell.* 221: 2008-2017.
- Youden, W. J. 1950. Index for rating diagnostic tests. *Cancer.* 3: 32-35.

Tables

Table 1: Results of the general and parsimonious GLM estimations for the Scallop Dredge VMS polls based on 50 percent of the trips resampled (with replacement) randomly 20 times.

	<i>Scallop Dredge</i>			
	<i>Full Model</i>		<i>Parsimonious Model</i>	
	<i>Coefficient</i>	<i>Robust standard error</i>	<i>Coefficient</i>	<i>Robust standard error</i>
Speed	-0.719 *** [-0.763; -0.688]	0.009 [0.008; 0.009]	-0.724 *** [-0.775; -0.693]	0.008 [0.008; 0.009]
VHP/length	0.051 *** [0.022; 0.084]	0.005 [0.005; 0.006]	0.055 *** [0.033; 0.090]	0.005 [0.005; 0.006]
VHP/length × Speed	0.104 *** [0.087; 0.123]	0.007 [0.006; 0.007]	0.102 *** [0.067; 0.139]	0.007 [0.006; 0.007]
Speed ²	-1.092 *** [-1.120; -1.059]	0.011 [0.010; 0.012]	-1.089 *** [-1.118; -1.062]	0.010 [0.009; 0.011]
Speed-Speed _{t-1}	0.006 [-0.007; 0.025]	0.006 [0.006; 0.006]		
Angle	0.016 * [0.004; 0.027]	0.005 [0.005; 0.005]	0.014 ** [0.004; 0.029]	0.005 [0.005; 0.005]
Position weight	0.008 [-0.018; 0.039]	0.013 [0.012; 0.013]		
Depth	-0.003 [-0.079; 0.041]	0.006 [0.004; 0.010]		
Depth-Depth _{t-1}	-0.024 * [-0.034; -0.011]	0.006 [0.006; 0.007]	-0.022 ** [-0.036; -0.009]	0.007 [0.005; 0.009]
Speed Range	-0.613 *** [-0.632; -0.579]	0.010 [0.009; 0.010]	-0.606 *** [-0.649; -0.560]	0.010 [0.009; 0.010]
Distance	0.020 * [-0.013; 0.044]	0.006 [0.006; 0.006]		
Distance ²	-0.006	0.004		

	[-0.030; 0.022]	[0.004; 0.005]		
4-7 o'clock	0.085 ***	0.019		
	[0.055; 0.135]	[0.018; 0.019]		
7-10 o'clock	0.332 ***	0.019		
	[0.270; 0.370]	[0.018; 0.019]		
10-13 o'clock	0.468 ***	0.019		
	[0.392; 0.527]	[0.019; 0.020]		
13-16 o'clock	0.529 ***	0.019		
	[0.481; 0.582]	[0.019; 0.020]		
16-19 o'clock	0.439 ***	0.019		
	[0.387; 0.493]	[0.019; 0.019]		
19-22 o'clock	0.289 ***	0.019		
	[0.240; 0.322]	[0.019; 0.019]		
22-1 o'clock	0.093 ***	0.019		
	[0.043; 0.140]	[0.018; 0.019]		
New Moon	0.050	0.037	0.061	0.037
	[-0.090; 0.142]	[0.035; 0.040]	[-0.024; 0.161]	[0.035; 0.039]
First Quarter	-0.120 *	0.036	-0.131 *	0.037
	[-0.223; -0.041]	[0.034; 0.038]	[-0.240; -0.021]	[0.034; 0.039]
Full Moon	0.071	0.037	0.095	0.037
	[-0.056; -0.194]	[0.035; 0.039]	[-0.046; 0.234]	[0.035; 0.039]
Last Quarter	0.010	0.039	-0.013	0.038
	[-0.109; 0.122]	[0.036; 0.042]	[-0.134; 0.087]	[0.036; 0.040]
Monday	-0.039	0.018		
	[-0.065; -0.002]	[0.018; 0.018]		
Tuesday	0.001	0.018		
	[-0.031; -0.048]	[0.018; 0.018]		
Wednesday	-0.034	0.018		
	[-0.082; 0.021]	[0.018; 0.018]		
Thursday	-0.045	0.018		

	[-0.089; -0.002]	[0.017; 0.018]		
Friday	-0.029	0.018		
	[-0.065; 0.011]	[0.017; 0.018]		
Saturday	-0.020	0.018		
	[-0.059; 0.017]	[0.017; 0.018]		
Monthly Dummies	YES		YES	
Yearly Dummies	YES		YES	
Constant	0.973 ***	0.035	1.220 ***	0.030
	[0.772; 1.203]	[0.032;0.037]	[0.862; 1.562]	[0.027; 0.034]
Observations	549,674		549,674	
AIC	253,534 [246,951; 266,960]		255,194 [247,183; 262,152]	
Condition Number	1085.64 [878.46; 1266.84]		361.17 [283.89; 453.91]	
VIF [min, max]	[1.004; 3.980]		[1.000; 3.732]	
Gradient [min, max]	[-8.64E-10; 1.63E-09]		[-6.46E-11; 7.37E-11]	
DW test	1.031 *** [1.002; 1.064]		1.028 *** [1.003; 1.051]	
Moran's I	0.000 [0.000; 0.000]		0.000 [0.000; 0.000]	
Geary's C	1.043 [0.900; 1.233]		1.036 [0.867; 1.196]	
LogLik	-143,442			
LR-test Chi2 (df)	84,107 *** (44) [-185,495]		1,879.4 *** (18) [-144,381]	
[LogLik]				

Note: The table reports the mean [minimum, maximum] coefficients, robust standard errors and indicators for the regression estimation. Significance codes: ‘***’ 0.001 ‘**’ 0.05 ‘*’ 0.1. Significant coefficients marked bold.

Table 2: Results of the general and parsimonious GLM estimations for the Sink Gillnet VMS polls based on 50 percent of the trips resampled randomly 20 times.

	<i>Sink Gillnet</i>			
	<i>Full Model</i>		<i>Parsimonious Model</i>	
	<i>Coefficient</i>	<i>Robust standard error</i>	<i>Coefficient</i>	<i>Robust standard error</i>
Speed	-0.744 *** [-0.788; -0.690]	0.014 [0.013; 0.016]	-0.800 *** [-0.851; -0.749]	0.013 [0.012; 0.013]
VHP/length	0.072 ** [0.008; 0.167]	0.012 [0.009; 0.019]	0.072 *** [0.033; 0.122]	0.010 [0.009; 0.014]
VHP/length × Speed	-0.008 [-0.056; 0.028]	0.011 [0.008; 0.015]		
Speed ²	-0.284 *** [-0.381; -0.204]	0.022 [0.021; 0.025]	-0.371 *** [-0.445; -0.312]	0.023 [0.021; 0.024]
Speed-Speed _{t-1}	-0.277 *** [-0.297; -0.255]	0.012 [0.012; 0.012]	-0.264 *** [-0.281; -0.249]	0.011 [0.011; 0.012]
Angle	0.024 * [0.008; 0.044]	0.009 [0.009; 0.010]	0.032 ** [0.006; 0.059]	0.009 [0.009; 0.009]
Position weight	0.021 [-0.008; 0.040]	0.010 [0.010; 0.011]		
Depth	-0.230 *** [-0.278; -0.133]	0.016 [0.012; 0.024]	-0.125 *** [-0.217; -0.074]	0.010 [0.009; 0.010]
Depth-Depth _{t-1}	0.008 [-0.013; 0.028]	0.012 [0.011; 0.013]		
Speed Range	0.196 *** [0.112; 0.250]	0.020 [0.020; 0.021]	0.052 * [0.003; 0.101]	0.019 [0.019; 0.020]
Distance	-0.071 [-0.252; 0.124]	0.046 [0.017; 0.088]		
Distance ²	0.066 [0.007; 0.139]	0.023 [0.005; 0.044]		

4-7 o'clock	0.550 ***	0.046		
	[0.466; 0.678]	[0.045; 0.050]		
7-10 o'clock	1.410 ***	0.045		
	[1.265; 1.567]	[0.043; 0.051]		
10-13 o'clock	1.078 ***	0.043		
	[0.932; 1.213]	[0.042; 0.047]		
13-16 o'clock	0.917 ***	0.044		
	[0.793; 1.029]	[0.043; 0.047]		
16-19 o'clock	0.907 ***	0.049		
	[0.741; 1.006]	[0.047; 0.052]		
19-22 o'clock	0.459 ***	0.051		
	[0.364; 0.525]	[0.049; 0.054]		
22-1 o'clock	0.164 ***	0.051		
	[0.100; 0.230]	[0.049; 0.054]		
New Moon	0.066	0.070	0.127	0.067
	[-0.075; 0.242]	[0.065; 0.075]	[-0.060; 0.350]	[0.061; 0.075]
First Quarter	-0.413 ***	0.078	-0.406 ***	0.078
	[-0.692; -0.107]	[0.072; 0.088]	[-0.689; -0.172]	[0.070; 0.087]
Full Moon	-0.179 *	0.065	-0.132	0.063
	[-0.374; 0.057]	[0.060; 0.070]	[-0.331; 0.067]	[0.058; 0.071]
Last Quarter	0.122	0.072	0.115	0.070
	[-0.052; 0.374]	[0.068; 0.079]	[-0.090; 0.357]	[0.066; 0.075]
Monday	-0.039	0.036		
	[-0.102; 0.039]	[0.035; 0.037]		
Tuesday	-0.020	0.035		
	[-0.119; 0.145]	[0.035; 0.037]		
Wednesday	-0.044	0.036		
	[-0.189; 0.071]	[0.035; 0.037]		
Thursday	-0.017	0.035		
	[-0.155; 0.098]	[0.034; 0.037]		

Friday	0.028 [-0.079; 0.133]	0.035 [0.034; 0.036]	
Saturday	0.016 [-0.060; 0.109]	0.035 [0.035; 0.037]	
Monthly Dummies	YES		YES
Yearly Dummies	YES		YES
Constant	-1.967 *** [-2.536; -1.594]	0.070 [0.065; 0.078]	-0.861 *** [-1.186; -0.553]
Observations	147,042		147,042
AIC	72,121 [67,500; 74,594]		73,871 [70,988; 77,920]
Condition Number	1375.81 [837.19; 1735.88]		521.27 [371.44; 663.12]
VIF [min, max]	[1.005; 4.700]		[1.004; 3.887]
Gradient [min, max]	[-8.35E-09; 1.34E-10]		[-9.75E-12; 8.92E-12]
DW test	1.222 *** [1.187; 1.283]		1.199 *** [1.152; 1.250]
Moran's I	0.008 [0.000; 0.028]		0.001 [0.000; 0.003]
Geary's C	1.007 [0.867; 1.216]		1.016 [0.744; 1.263]
LogLik	-36,393		
LR-test Chi2 (df)	15,986 *** (44) [-44,386]		2,419.8*** (12) [-37,603]
[LogLik]			

Note: The table reports the mean [minimum, maximum] coefficients, robust standard errors and indicators for the regression estimation. Significance codes: '****' 0.001 '***' 0.05 '**' 0.1. Significant coefficients marked bold.

Table 3: Results of the general and parsimonious GLM estimations for the Bottom Otter Trawl VMS polls based on 50 percent of the trips resampled randomly 20 times.

	<i>Bottom Otter Trawl</i>			
	<i>Full Model</i>		<i>Parsimonious Model</i>	
	<i>Coefficient</i>	<i>Robust standard error</i>	<i>Coefficient</i>	<i>Robust standard error</i>
Speed	-1.215 *** [-1.258; -1.160]	0.013 [0.012; 0.013]	-1.223 *** [-1.255; -1.198]	0.013 [0.012; 0.013]
VHP/length	-0.032 ** [-0.052; -0.005]	0.005 [0.005; 0.006]	-0.031 ** [-0.059; -0.005]	0.005 [0.005; 0.006]
VHP/length × Speed	0.177 *** [0.156; 0.204]	0.008 [0.007; 0.009]	0.181 *** [0.149; 0.208]	0.008 [0.007; 0.009]
Speed ²	-1.760 *** [-1.811; -1.717]	0.018 [0.017; 0.019]	-1.812 *** [-1.853; -1.769]	0.018 [0.017; 0.020]
Speed-Speed _{t-1}	-0.033 *** [-0.042; -0.024]	0.006 [0.006; 0.006]	-0.039 *** [-0.047; -0.030]	0.006 [0.006; 0.006]
Angle	-0.001 [-0.010; 0.007]	0.004 [0.004; 0.004]		
Position weight	0.027 ** [0.007; 0.040]	0.010 [0.009; 0.010]	0.061 *** [0.049; 0.086]	0.010 [0.010; 0.010]
Depth	-0.248 *** [-0.304; -0.196]	0.007 [0.006; 0.008]	-0.237 *** [-0.275; -0.208]	0.007 [0.006; 0.008]
Depth-Depth _{t-1}	0.035 *** [0.027; 0.048]	0.007 [0.006; 0.008]	0.036 *** [0.028; 0.046]	0.007 [0.007; 0.008]
Speed Range	0.164 *** [0.144; 0.186]	0.009 [0.009; 0.010]	0.116 *** [0.095; 0.141]	0.009 [0.009; 0.010]
Distance	-0.005 [-0.029; 0.024]	0.006 [0.005; 0.007]	-0.037 *** [-0.061; -0.009]	0.006 [0.005; 0.006]
Distance ²	-0.052 *** [-0.076; -0.017]	0.004 [0.003; 0.006]	-0.041 *** [-0.061; -0.015]	0.004 [0.003; 0.005]

4-7 o'clock	0.291 ***	0.016
	[0.264; 0.308]	[0.016; 0.016]
7-10 o'clock	0.789 ***	0.016
	[0.757; 0.829]	[0.016; 0.017]
10-13 o'clock	0.716 ***	0.016
	[0.660; 0.764]	[0.016; 0.017]
13-16 o'clock	0.622 ***	0.016
	[0.570; 0.678]	[0.016; 0.017]
16-19 o'clock	0.589 ***	0.017
	[0.563; 0.620]	[0.016; 0.017]
19-22 o'clock	0.249 ***	0.016
	[0.215; 0.287]	[0.016; 0.016]
22-1 o'clock	0.103 ***	0.016
	[0.081; 0.131]	[0.015; 0.016]
New Moon	-0.010	0.032
	[-0.089; 0.078]	[0.030; 0.033]
First Quarter	0.050	0.032
	[-0.056; 0.128]	[0.030; 0.034]
Full Moon	-0.020	0.031
	[-0.116; 0.072]	[0.029; 0.032]
Last Quarter	0.031	0.033
	[-0.041; 0.109]	[0.031; 0.036]
Monday	-0.007	0.015
	[-0.061; 0.024]	[0.015; 0.016]
Tuesday	0.002	0.015
	[-0.040; 0.067]	[0.015; 0.016]
Wednesday	-0.017	0.015
	[-0.050; 0.019]	[0.015; 0.016]
Thursday	-0.043 *	0.016
	[-0.090; 0.012]	[0.015; 0.016]

Friday	0.021 [-0.030; 0.059]	0.016 [0.015; 0.016]	
Saturday	0.020 [-0.008; 0.052]	0.015 [0.015; 0.015]	
Monthly Dummies	YES		YES
Yearly Dummies	YES		YES
Constant	0.558 *** [0.452; 0.628]	0.024 [0.024; 0.025]	1.027 *** [0.909; 1.103]
Observations	933,896		933,896
AIC	343,446 [335,533; 353,580]		346,314 [337,680; 358,646]
Condition Number	600.01 [514.90; 711.68]		398.24 [171.45; 484.74]
VIF [min, max]	[1.002; 2.216]		[1.026; 2.135]
Gradient [min, max]	[-2.00E-09; 2.02E-09]		[-1.78E-10; 1.84E-10]
DW test	0.951 *** [0.934; 0.963]		0.934 *** [0.911; 0.945]
Moran's I - Statistic	0.001 [0.000; 0.004]		0.000 [0.000; 0.004]
Geary's C	1.023 [0.995; 1.062]		1.028 [0.995; 1.069]
LogLik	-187,608		
LR-test Chi2 (df) [LogLik]	240,584 *** (44) [-307,901]		4,553.9 *** (18) [-189,885]

Note: The table reports the mean [minimum, maximum] coefficients, robust standard errors and indicators for the regression estimation. Significance codes: '***' 0.001 '**' 0.05 '*' 0.1. Significant coefficients marked bold.

Table 4: Indicators on the classification quality following the speed rule approaches of Palmer & Wigley (2009) and Lee et al. (2010) compared to the GLM predictions.

	<i>Palmer & Wigley (2009)</i>	<i>Lee et al. (2010)</i>	<i>GLM</i>
Scallop Dredge			
<i>Youden's J threshold: 0.623</i>			
True-positive (in %)	64.55	88.07	80.34
False-positive (in %)	35.86	65.80	38.11
AUC (in %)	64.34	61.13	77.90 [77.89; 77.90]
<i>Trip-specific threshold</i>			
True-positive (in %)	63.02	86.61	81.07
False-positive (in %)	36.08	64.87	45.84
Sink Gillnet			
<i>Youden's J threshold: 0.590</i>			
True-positive (in %)	54.96	41.23	80.26
False-positive (in %)	22.86	47.34	39.55
AUC (in %)	66.05	46.94	76.23 [76.22; 76.24]
<i>Trip-specific threshold</i>			
True-positive (in %)	52.34	39.63	78.22
False-positive (in %)	21.90	45.90	45.26
Bottom Otter Trawl			
<i>Youden's J threshold: 0.659</i>			
True-positive (in %)	82.98	95.74	88.93
False-positive (in %)	19.06	71.71	25.18
AUC (in %)	81.96	62.02	88.14 [88.11; 88.16]
<i>Trip-specific threshold</i>			
True-positive (in %)	82.77	86.61	92.33
False-positive (in %)	18.41	64.87	31.14

Note: Comparison is conducted by either using the gear group specific calculated Youden's J threshold or by trip specific thresholds to classify the fitted values.

Figures

Fig. 1: Spatial distribution of VMS polls which belong to a fishing haul according to observer data (left) and according to GLM prediction using the Youden's J Index as threshold (right) for Scallop Dredge trips (FY 2010-14).

Fig. 2: Spatial distribution of VMS polls which belong to a fishing haul according to observer data (left) and according to GLM prediction using the Youden's J Index as threshold (right) for Sink Gillnet trips (FY 2010-14).

Fig. 3: Spatial distribution of VMS polls which belong to a fishing haul according to observer data (left) and according to GLM prediction using the Youden's J Index as threshold (right) for Bottom Otter Trawl trips (FY 2010-14).

Fig. 4: ROC graph for Scallop Dredge prediction vs. speed rules

The ROC based on a random sample of one prediction for each observation are plotted next to the ROC curves based on the classification of the speed rule by Palmer & Wigley (2009) and Lee et. al. (2010). The 95 percent confidence interval of the GLM prediction is plotted in grey, however, due to the low variation, the curve of the prediction overlays the curves on the upper and lower boundaries of the predictions. The grey line is the 45-degree line.

Fig. 5: ROC graph for Sink Gillnet prediction vs. speed rules

The ROC based on a random sample of one prediction for each observation are plotted next to the ROC curves based on the classification of the speed rule by Palmer & Wigley (2009) and Lee et. al. (2010). The 95 percent confidence interval of the GLM prediction is plotted in grey, however, due to the low variation, the curve of the prediction overlays the curves of the upper and lower boundaries of the predictions. The grey line is the 45-degree line.

Fig. 6: ROC graph for Bottom Otter Trawl prediction vs. speed rule

The ROC based on a random sample of one prediction for each observation are plotted next to the ROC curves based on the classification of the speed rule by Palmer & Wigley (2009) and Lee et. al. (2010). The 95 percent confidence interval of the GLM prediction is plotted in grey, however, due to the low variation, the curve of the prediction overlays the curves of the upper and lower boundaries of the predictions. The grey line is the 45-degree line.

Appendix

Table A1: Descriptive Statistics

<i>Overall dataset</i>	<i>FY</i>	<i>2010</i>	<i>2011</i>	<i>2012</i>	<i>2013</i>	<i>2014</i>	<i>overall</i>
Scallop Dredge							
Number of trips		306	375	411	456	445	1.993
Number of VMS polls		100,014	119,042	154,320	116,853	109,826	600,055
Ratio of observed fishing to non-fishing VMS polls		1.163	1.096	1.347	0.647	0.628	0.953
Average time between polls (in h)		0.478	0.477	0.472	0.483	0.477	0.477
Sink Gillnet							
Number of trips		1,886	2,029	1,335	896	1,165	7,311
Number of VMS polls		37,779	45,633	29,974	25,548	32,329	171,263
Ratio of observed fishing to non-fishing VMS polls		0.442	0.611	0.453	0.628	0.597	0.542
Average time between polls (in h)		0.707	0.658	0.673	0.661	0.666	0.673
Bottom otter trawl							
Number of trips		1,888	2,230	1,702	1,465	1,449	8,734
Number of VMS polls		220,595	284,773	171,262	173,948	172,233	1,022,811
Ratio of observed fishing to non-fishing VMS polls		1.197	1.411	1.426	1.317	1.171	1.306
Average time between polls (in h)		0.560	0.530	0.538	0.540	0.532	0.540

Scallop Dredge					
	N	mean	Std. Dev.	Min	Max
Speed (in km/h)	549,674	7.167	4.678	0	39.723
Speed-Speed _{t-1}	549,674	0.015	3.514	-32.970	37.335
Angle (in rad)	549,674	2.877	1.893	0	6.283
Position weight	549,674	0.054	0.37	0	4
Depth (in m)	549,674	-57.706	74.821	-3,163	-1
Depth-Depth _{t-1}	549,674	0.006	9.904	-1,022	875
Speed Range	549,674	0.480	0.5	0	1
Distance (in km)	549,674	733.37	481.22	0.027	3,721.37
Month (Date landed)	549,674	6.343	2.752	1	12
Daytime (3h interval)	549,674	4.527	2.282	1	8
Weekday	549,674	3.023	1.994	0	6
Moon phase	549,674	0.167	0.684	0	4
VHP/length	549,674	9.492	2.949	4.280	29.172
Trip duration (in h)	549,674	217.521	81.383	5	406.667
Time between VMS polls (in h)	549,674	0.469	0.146	0.0003	3
Observed VMS fishing polls	549,674	0.491	0.500	0	1

<i>Sink Gillnet</i>					
	N	mean	Std. Dev.	Min	Max
Speed (in km/h)	147,042	6.853	6.552	0	37.363
Speed-Speed _{t-1}	147,042	0.206	5.414	-34.861	35.471
Angle (in rad)	147,042	3.110	1.840	0	6.283
Position weight	147,042	0.355	0.907	0	4
Depth (in m)	147,042	-93.381	60.234	-306	-1
Depth-Depth _{t-1}	147,042	-0.074	21.836	-173	171
Speed Range	147,042	0.469	0.499	0	1
Distance (in km)	147,042	135.40	136.31	0.008	2,519.87
Month (Date landed)	147,042	7.077	3.027	1	12
Daytime (3h interval)	147,042	4.012	1.898	1	8
Weekday	147,042	3.057	1.946	0	6
Moon phase	147,042	0.175	0.708	0	4
VHP/length	147,042	7.556	3.137	0.028	62.5
Trip duration (in h)	147,042	55.870	60.966	1	306.5
Time between VMS polls (in h)	147,042	0.678	0.333	0.001	3
Observed VMS fishing polls	147,042	0.375	0.484	0	1

<i>Bottom Otter Trawl</i>					
	N	mean	Std. Dev.	Min	Max
Speed (in km/h)	933,896	7.093	4.462	0	39.681
Speed-Speed _{t-1}	933,896	0.016	2.835	-35.487	36.759
Angle (in rad)	933,896	2.944	1.884	0	6.283
Position weight	933,896	0.073	0.427	0	4
Depth (in m)	933,896	-122.251	96.458	-2,658	-1
Depth-Depth _{t-1}	933,896	-0.001	28.972	-1,158	1,076
Speed Range	933,896	0.679	0.467	0	1
Distance (in km)	933,896	501.500	384.440	0.006	4,874.64
Month (Date landed)	933,896	6.556	3.557	1	12
Daytime (3h interval)	933,896	4.446	2.234	1	8
Weekday	933,896	2.990	2.004	0	6
Moon phase	933,896	0.170	0.693	0	4
VHP/length	933,896	8.702	3.111	0	29.172
Trip duration (in h)	933,896	145.970	75.803	2	606.667
Time between VMS polls (in h)	933,896	0.540	0.247	0.001	3
Observed VMS fishing polls	933,896	0.575	0.494	0	1