Quantitative and qualitative comparison of three wet aggregate stability methods using a long-term tillage system and crop rotation experiment

Journal:	<i>Canadian Journal of Soil Science</i>
Manuscript ID	CJSS-2018-0101.R2
Manuscript Type:	Short Communication
Date Submitted by the Author:	09-Oct-2018
Complete List of Authors:	Van Eerd, Laura; University of Guelph Ridgetown Campus, School of Environmental Sciences DeBruyn, Amanda; University of Guelph Ridgetown Campus, School of Environmental Sciences Ouellette, Lance; University of Guelph School of Environmental Sciences Hooker, David; University of Guelph Ridgetown Campus,, Plant Agriculture; University of Guelph Robinson, Darren; University of Guelph, Dept. Plant Agriculture
Keywords:	Aggregates, Tillage, Crop rotation, Soil quality
Is the invited manuscript for consideration in a Special Issue?:	Not applicable (regular submission)

SCHOLARONE™
Manuscripts

Short communication

Quantitative and qualitative comparison of three wet aggregate stability methods using a long-term tillage system and crop rotation experiment.

L. L. Van Eerd¹, A. H. DeBruyn¹, L. Ouellette¹, D. C. Hooker², and D. E. Robinson². ¹School of Environmental Sciences, University of Guelph, Ridgetown Campus, Ridgetown, Ontario, N0P 2C0. ²Department of Plant Agriculture, University of Guelph, Ridgetown Campus, Ridgetown, Ontario, N0P 2C0.

Abstract

Automated wet sieving (AWS) is preferred for this clay loam soil due to better sensitivity and savings (time, disposables) despite a larger capital investment. Rotations with greater frequency of winter wheat and no-till compared with conventional plow system had greater wet aggregate stability (WAS) values indicating better surface soil quality.

Key Words: soil sampling methods, soil quality, soil health, winter wheat, soybean, no-till, plow tillage

Short Title: Wet aggregate stability methods

Abbreviations: AWS, automated wet sieving; CSW, corn-soybean-winter wheat rotation; HWS, hand wet sieving; RFS, rainfall simulator; SOY, continuous soybean; SW, soybean-winter wheat rotation; WAS, wet aggregate stability

The desire to increase agricultural productivity and resilience has led to a focus on best management practices that improve soil quality. The ability to identify changes in soil quality requires sensitive and feasible soil indicators (Karlen et al. 2013). Aggregate stability is one suitable soil quality indicator, as it is affected by several interacting factors such as microbial activity, organic matter content, content of clay and clay mineralogy, and the presence of calcium carbonate. Therefore, further development of aggregate stability as an indicator may provide insights into soil quality and influential agricultural management practices.

There is no consistent measurement of aggregate stability. There are several methods to characterize aggregate stability through the measurements of water stable aggregates, mean weight diameter, and geometric mean diameter (e.g., Saygin et al. 2012). For instance, an automatic wet sieving (AWS) method by Kemper and Rosenau (1986) is widely used and emulates natural destructive forces by submerging aggregates repeatedly in liquid using a single sieve apparatus. Pojasok and Kay (1990) modified a hand, wet sieving (HWS) aggregate stability method. More recently, a rainfall simulator (RFS) method emulated the force of a heavy rainfall after surface drying (Idowu et al. 2008). All three methods estimate wet aggregate stability (WAS) with various soil sampling and pre-treatment requirements.

Single sieve, multiple sieve, and rainfall simulator methods each have corresponding advantages and disadvantages. Moreover, method accuracies have been found to fluctuate with soil texture (Lado et al. 2004). Therefore, determining which method may be the most sensitive for detecting real differences in aggregate stability is important. Furthermore, little information is available on the effect of differing soil sampling methods on aggregate

stability estimates. Determining which method is the least laborious and the most sensitive for detecting differences in WAS across agricultural management systems may help to improve soil aggregate testing techniques in the future. Thus, we evaluated three wet-sieving methods and two soil sampling methods in terms of resource efficiency (e.g., time and costs) and sensitivity to detect changes in aggregate stability due to agricultural management using a 22-yr long-term experiment at Ridgetown, Ontario.

MATERIALS AND METHODS

The long-term tillage system and crop rotation experiment (est. 1995) at Ridgetown, ON (latitude 42°26'26"N longitude 81°53'3"W) was utilized because previous research identified differences in various soil quality attributes including WAS (Van Eerd et al. 2014; Congreves et al. 2015). Field treatments were arranged in a split-plot design with four replicates. Main effects were no-till (zone-till for grain corn (*Zea mays* L.)) and conventional tillage (fall plow with spring secondary tillage), and three crop rotations were sampled in the soybean (*Glycine max* L.) phase: corn-soybean-winter wheat (*Triticum aestivum* L.) [CSW], soybean-winter wheat [SW], and continuous soybean [SOY]. Soil samples were collected in 24 experimental units from the fertilizer nitrogen treatment-subplots of 100 kg N ha⁻¹ applied to the winter wheat crop and 120 kg N ha⁻¹ to the grain corn crop. For crop production details see Van Eerd et al. (2014).

Soil Sampling

Soil (clay loam, Orthic Humic Gleysol) was collected on 26 June 2013 at a 0-15 cm depth using two methods. For the probe method, one composite soil sample per experimental unit consisted of fifteen cores per experimental unit was taken using a 3.5 cm diameter soil

probe. Similarly, for the ring method, one composite sample was taken per experimental unit but consisted of three 7.5 cm diameter ring-cores typically used for bulk density measurements. In the field, soil was homogenized by hand; plant debris and stones were removed; and partitioned into three subsamples - one for each aggregate stability method.

Aggregate Stability Methods.

Automated Wet-Sieving (AWS) Method

According to Kemper and Rosenau (1986), field moist soil was hand-sieved (4mm) and air-dried for one week at room temperature (22.5°C). Using an automatic sieving apparatus (Eijkelkamp Agrisearch Equipment 08.13. Giesbeek, Netherlands), 4 g soil was placed in sieve (0.25 mm) cups, lightly re-wetted for 1 min with 1 mL distilled water spray. Soil was subjected to 3 min of repetitive submersion into 100 mL distilled water, then sieved two more times in 100 mL NaOH for 10 min each. Soil slaked into both solutions were filtered (Whatman 42), oven dried (105°C) for at least 12 hr, and weighed. Data were expressed as mean weight diameter.

Hand-Wet Sieving (HWS) Method

This method was according to Pojasok and Kay (1990). Briefly, field-moist soil was passed through a 4-mm sieve. Soil (5 g) was placed on filter paper (Whatman 42, 3 cm by 5 cm) and wetted for 90 minutes on a Mariotte bottle wetting table. Soil in distilled water (40 mL) was agitated at 0.8 diameter 25 rpm for 10 minutes on an Eberbach shaker. Soil was sieved (0.25 mm) and rinsed with an additional 40 mL of distilled water. Slaked soil left on sieves was oven dried (105°C) for 24 hr, weighed, and subjected to 5 mL sodium hexametaphosphate (NaPO_3)₆ at 5% concentration for 4 hr prior to sieving and weighing the resulting fractions. Data were expressed as the percent weight of stable aggregates

relative to total weight and corrected for sand ($>250\ \mu\text{m}$) content. Additional dispersible clay readings suggested by Pojasok and Kay (1990) were not completed.

Rainfall Simulator (RFS) Method

Soil was oven-dried at 40°C for 72 hours (constant weight) and 40 g shaken for 10 min over 8 mm, 2 mm, and 0.25 mm sieves. The resulting $<2\ \text{mm}$ and $>0.25\ \text{mm}$ fraction was subjected to 5 min of rainfall (500 mm; individual drops approx. 4 mm in diameter with an estimated total impact of 0.74 J) using a RFS apparatus (source: Cornell University) according to Idowu et al. (2009). For RFS, data were expressed as the percent weight of stable aggregate of the total weight (0.25 to 2 mm fraction).

Qualitative Analysis of Soil Sampling and Aggregate Stability Methods

To assess sensitivity, laboriousness and costs, each method was evaluated using seven criteria (Table 1) on a relative indexing score of low, intermediate and high. Sensitivity was based on data variability (coefficient of variability and sample standard deviation) and statistical differences among treatments. Laboriousness was assessed according to (i) complexity of set up and the number of steps required, (ii) time required to process samples expressed as the number of samples processed per run and (iii) storage requirements. Costs include equipment and disposables but not labour costs.

Statistical Analysis

All analyses were conducted in SAS (SAS Institute, version 9.2, Cary, NC, USA). Data met all ANOVA assumptions; no transformations were required. Initial 4-way ANOVA of soil sampling method, aggregate stability method, tillage system and crop rotation revealed no impact of soil sampling method ($P = 0.2866$) nor interactions containing soil sampling method ($P \geq 0.2041$), therefore a 3-way analysis was conducted without soil sampling

method effect. Using a mixed model (PROC MIXED), fixed effects included aggregate stability method, tillage, crop rotation, and their respective interactions. Random effects were block and block by tillage to account for the split plot design with tillage as the main effect and crop rotation as the sub-plot effect. Treatment differences were separated using a Tukey-Kramer least significant difference test with an alpha value of 0.05. To determine relationships among WAS methods, linear correlations were conducted (PROC CORR).

RESULTS AND DISCUSSION

Mean WAS values ($\pm$ SE) were not influenced by soil sampling method (probe $49.8 \pm 1.74\%$; ring $51.1 \pm 1.77\%$). The WAS measurements from the two soil sampling methods were highly correlated ($r = 0.851$; $P < 0.0001$). The lack of interactions of sampling method with all other effects ($P > 0.2041$) and similar variability in the data (probe CV = 29.4%; ring CV=29.6%), suggests that either method would be appropriate on this soil. Based on these results, the probe method may be preferred because it is less laborious (Table 1), unless bulk density measurements via ring-core samples are needed.

Despite a higher initial capital investment, AWS was less costly (time and disposable) and less laborious than the other two WAS methods (Table 1). In addition, AWS requires less bench-top space and can be completed at any time after soil was dried. The HWS method takes more time per sample and must be completed on field moist soil, thus should be processed in a timely manner. The constraining factors of the RFS method were the large space requirement and the ability to contain/remove large volumes of water (e.g., a floor drain). All methods require minimal training, but the AWS minimizes human error

due to its simple procedure and automated nature. Thus, based on effort, the AWS is preferred.

For all three WAS methods, surface soil WAS was greater in the no-till (avg. $54.3\% \pm 1.08$) than conventional fall plow system (avg. $46.7\% \pm 1.08$) (Fig. 1), which agreed with previous WAS results at Ridgetown (Van Eerd et al. 2014) and other long-term trials in Ontario (Congreves et al. 2015). This indicates better surface soil quality with no-till than fall plow conventional systems. The magnitude of differences in WAS between tillage systems was smallest with HWS (no-till avg. $51.0\% \pm 1.70$, plow tillage avg. $45.6\% \pm 1.70$), suggesting lesser sensitivity (Fig. 1).

Only the RFS method detected a tillage system by crop rotation interaction ($P = 0.0151$). The interaction was due to a lack of difference between tillage systems in the SW rotation (42.2 and $42.8\% \pm 3.37$) but greater WAS values with no-till than conventional systems in the other two rotations. With RFS method, the smallest WAS values were in SOY under conventional tillage ($27.2\% \pm 3.37$), which was not different than CSW under conventional tillage ($33.2\% \pm 3.37$). These results were consistent with other soil quality indicators (Van Eerd et al. 2014; Congreves et al. 2017) as well as corn and soybean productivity and resiliency with winter wheat in the rotation (Gaudin et al. 2015).

The WAS method by crop rotation interaction ($P = 0.0003$) was attributed to the lack of rotation effect in HWS but differences among crop rotations with the other two methods (Fig. 1). Thus, the ability to detect crop rotation differences in WAS depended on the method used. Trends among crop rotations were consistent with all methods; WAS values were greatest in SW and smallest in SOY rotations. This result agreed with other locations

and other soil quality indicators (Van Eerd et al. 2014; Congreves et al. 2015) and demonstrates the positive influence of winter wheat on soil quality.

The RFS method had the greatest variability followed by AWS and HWS (e.g., CV = 24.7, 18.0, and 13.7 %, respectively). Although RFS and HWS were not correlated ($r = 0.00971$; $P > 0.05$), the AWS method was correlated with RFS ($r = 0.492$; $P < 0.001$) and HWS ($r = 0.325$; $P < 0.05$). The relatively weak correlations among methods was surprising but likely reflects the observed differences in quantifying WAS among methods.

The most significant outcome of this research was that interpretation of the impact of agricultural management practices on soil structure depended on the WAS measurement method employed. The AWS method had the lowest variability and the greatest sensitivity in detecting differences among agricultural management practices and greater correlations with the other two methods. Influencing factors of AWS method may include the automation of the wet sieving process that reduces human error, the air-dried pre-treatment which may mimic field drying conditions, and pre-misting to moisten aggregates which would prevent bursting upon contact with water. Moreover, compared with the other two methods, AWS was simple to conduct and time efficient with minimal disposable costs after initial investment. Overall, the AWS method by Kemper and Rosenau (1986) was the preferred method to quantify WAS on this clay loam soil of contrasting soil quality.

Acknowledgements.

Authors acknowledge the following for their guidance in the field and laboratory: A.E. Verhallen, S. Jay, M. Zink, and M.A. Rojas.

- Congreves, K. A., Hooker, D. C., Hayes, A., Verhallen, E. A. and Van Eerd, L. L. 2017. Interaction of long-term nitrogen fertilizer application, crop rotation, and tillage system on soil carbon and nitrogen dynamics. *Plant Soil* **410**: 113-127.
- Congreves, K. A., Hayes, A., Verhallen, E. A. and Van Eerd, L. L. 2015. Long-term impact of tillage and crop rotation on soil health at four temperate agroecosystems. *Soil Tillage Res.* **152**: 17-25.
- Gaudin, A. C. M., Tolhurst, T. N., Ker, A. P., Janovicek, K., Tortora, C., Martin, R. C. and Deen, W. 2015. Increasing crop diversity mitigates weather variations and improves yield stability. *PLoS One* **10**: e0113261.
- Idowu, O. J., van Es, H. M., Abawi, G. S., Wolfe, D. W., Ball, J. I., Gugino, B. K., Moebius, B. N., Schindelbeck, R. R. and Bilgili, A. V. 2008. Farmer-oriented assessment of soil quality using field laboratory, and VNIR spectroscopy methods. *Plant Soil* **307**: 243-253.
- Karlen, D. L., Kovar, J. L., Cambardella, C. A. and Colvin, T. S. 2013. Thirty-year tillage effects on crop yield and soil fertility indicators. *Soil Till. Res.* **130**: 24-41.
- Kemper, W. D. and Rosenau, R. C. 1986. Aggregate stability and size distribution. Pg. 425-442 in A. Klute eds. *Methods of soil analysis. Part 1*. 2nd ed. Agronomy Monograph. 9. ASA and SSSA, Madison, WI.
- Lado, M., Ben-Hur, M. and Shainberg, I. 2004. Soil wetting and texture effects on aggregate stability, seal formation, and erosion. *Soil Sci. Soc. Am. J.* **68**: 1992-1999.
- Pojasok, T. and Kay, B. 1990. Assessment of a combination of wet sieving and turbidimetry to characterize the structural stability of moist aggregates. *Can. J. Soil. Sci.* **70**: 33-42.
- Saygin, S. D., Cornelis, W. M., Erpul, G. and Gabriels, D. 2012. Comparison of different aggregate stability approaches for loamy sand soils. *Applied Soil Ecol.* **54**: 1-6.

Van Eerd, L. L., Congreves, K. A., Hayes, A., Verhallen, E. A. and Hooker, D. C. 2014. Long-term tillage and crop rotation effects on soil quality, organic carbon, and total nitrogen. *Can. J. Soil Sci.* **94**: 303-315.

List of Figure Captions:

Fig. 1. Wet aggregate stability (WAS) (%) as influenced by rainfall, automated and hand measurement methods and affected by tillage system (top) and crop rotation (bottom). Boxplots show 25th, 50th, and 75th percentiles, whiskers indicate 10th and 90th percentiles, circles are outliers and 'x' depicts average. Different uppercase letters indicate statistical differences of mean WAS values among crop rotations or between tillage systems (above the x-axes) and among WAS measurement methods (above the legend) ($P < 0.05$). For each panel, different lowercase letters within each method indicate significant differences among tillage system ($n=24$) or crop rotation ($n=16$) treatments. soy, continuous soybean; sw, soybean-winter wheat; csw, corn-soybean-winter wheat. Note: there was a tillage system by crop rotation interaction for the rainfall simulator method only.

Table 1. Qualitative analysis of soil sampling and aggregate stability method.

Procedure	Method ^a	Sensitivity ^b	Complexity: preparation	Complexity: procedures	Storage: Ease + space required	Time required (samples / day) ^c	Cost: equipment	Cost: disposables
Sampling	Probe	High	Low	Low	High	Low	Low	None
	Ring	High	Intermediate	Intermediate	Intermediate	High	Low	None
Aggregate	AWS	High	Low	Intermediate	High	Low (32 in 2 d)	High	Low
Stability	HWS	Intermediate	High	High	Low	High (16 in 2.5 d)	Intermediate	Intermediate
	RFS	Low	Intermediate	Intermediate	High	High (24 in 4.5 d)	Intermediate	High

^a Probe: 15 cores 3.5-cm diameter; Ring: 3 cores 10-cm diameter; AWS, automated wet sieving; HWS, hand-wet sieving; RFS, rainfall simulator.

^b Includes variability in data and ability to detect agricultural management differences.

^c Includes set up and clean up time assuming equipment was assembled.